

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	



Valve control unit C-TOP-1711

Applications

The C-TOP-1711 is a straight-stroke pneumatic valve control unit designed for valve process control. It is compatible with most PLC (programmable logic controller) automation systems with digital communication or bus communication (AS-I BUS). Including position feedback output, two-stage LED light display, anti-leak function, valve opening and closing control, etc., used to control all types of process valves. It can be installed on various pneumatic valves, such as pneumatic butterfly valves, ball valves, diaphragm valves, angle seat valves, globe valves, reversing valves, etc...

Functions

Control input: PNP DC 24V

Feedback Output : PNP DC 24V & 4-20mA

Power supply : DC24V ± 10%

Bus communication : AS-I-BUS

Accuracy: repeat positioning accuracy ≤ 0.5mm;

Setting: One-button auto-tuning function

Operating mode: automatic & manual

Leak prevention diagnostic function

Display: two-segment lamp color

Open: green / red

Close: red / green

Stroke range: 0-30mm



Valve control unit-C-TOP-1881

Applications

C-TOP-1881 is a straight-stroke pneumatic valve control unit designed for valve process control. It is compatible with most PLC (programmable logic controller) automation systems with digital communication or bus communication (AS- I BUS). Including position feedback output, two-stage LED light display, anti-leak function, valve opening and closing control, etc., used to control all types of process valves. It can be mounted on a variety of pneumatic valves, such as pneumatic butterfly valves, ball valves, diaphragm valves, angle seat valves, globe valves, reversing valves, etc.....

Functions

Control input: PNP DC 24V

Feedback Output : PNP DC 24V

Power supply : DC24V ± 10%

Bus communication : AS-I-BUS

Accuracy: Repeat positioning accuracy ≤ 0.2%;

Setting: One-button auto-tuning function

Operating mode: automatic & manual

Leak prevention diagnostic function

Display: two-segment lamp color

Open: green / red

Close: red / green

Travel range: 0-60mm/0-30mm



Valve control unit C-TOP-1721

Applications

The C-TOP-1721 is a straight-stroke pneumatic valve control unit designed for valve process control. It is compatible with most PLC (programmable logic controller) automation systems with digital communication or bus communication (AS-I BUS). Including position feedback output, three-segment LED display, anti-leak function, valve opening and closing control, etc., used to control all types of process valves. It can be installed on various pneumatic valves, such as pneumatic butterfly valves, ball valves, diaphragm valves, angle seat valves, globe valves, reversing valves, mixing proof valves, etc.

Functions

Control input: PNP DC 24V

Feedback Output : PNP DC 24V & 4-20mA

Power supply : DC24V ± 10%

Bus communication : AS-I-BUS

Accuracy: repeat positioning accuracy ≤ 0.5mm;

Setting: One-button auto-tuning function

Operating mode: automatic & manual

Leak prevention diagnostic function

Display: three-segment lamp color

Open: green / red

Close: red / green

Middle position: yellow, suitable for anti-mix valve

Travel range: 0-60mm



Valve control unit C-TOP-1561

Applications

C-TOP-1561 is a rotary angular stroke pneumatic valve control unit designed for valve process control. It is compatible with most PLC (programmable logic controller) automation systems with digital communication or bus communication (AS). -I BUS). Including position feedback output, two-stage LED light display, anti-leak function, valve opening and closing control, etc., used to control all types of process valves. It can be installed on various pneumatic valves, such as pneumatic butterfly valves, ball valves, globe valves and other rotary stroke valves.....

Functions

Control input: PNP DC 24V

Feedback Output : PNP DC 24V & 4-20mA

Power supply : DC24V ± 10%

Bus communication : AS-I-BUS

Accuracy: Repeat positioning accuracy ≤ 0.2%;

Setting: One-button auto-tuning function

Operation: Automatic & Manual

Leak prevention diagnostic function

Display: two-segment lamp color

Open: green / red

Close: red / green

Stroke angle: 0-180°



Valve control unit-C-TOP-0821 (Phase out)

Applications

C-TOP is a controller which combines the signaling and devices command to monitor all types of (piston) process valves. The controller (in a single component) includes the following features:

- Green: valve is open
- Red: valve is closed
- Yellow: valve is in progress of the third position (mixproof valve) operation

Technical specifications

Actuator: 1) single-action 2) double-action 3) triple action

Bus version: AS-I BUS

Basic version: cable connection

Power: DC 24V ± 10%

Air supply: 4-7Bar

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	